

# The 4G communicating watch dedicated to your safety!

Teleworking Logistics Field Based Maintenance Retail Utilities

Ideal for responding quickly and simply to a safety problem. Equip your employees with an ergonomic device incorporating the Emerit© alert application Emerit© designed for professionals exposed to risky situations: isolation - lone worker protection, teleworking, dangerous areas (injury, discomfort, fall), verbal or physical aggression.



### e - WG 100

### > Transmission of alarms

# VIA GSM NETWORK with SIM card

### **2G | 3G | 4G VOICE & DATA**

All operators

- Calls
- SMS
- SIA DC-09 Protocol

# **VIA WIFI NETWORK** without SIM card

#### **WIFI 2.4 GHz VOICE & DATA**

802.11n / Voice over IP with SIP account

- Calls
- SIP messages / SMS
- SIA DC-09 protocol

### > Location of alarms



#### **OUTDOORS BY SATELLITE**

GSM Network needed to transmit the alarm containing GPS position



### **INDOORS VIA WIFI**

Via the existing network on site GSM or Wifi network required to transmit alarms containing indoor location



### **INDOORS VIA BLUETOOTH**

With the implementation of Bluetooth beacons GSM or Wifi network required to transmit alarms containing indoor location

### > Bluetooth beacon

# THE CONFIGURATION OF YOUR PREMISES REQUIRES A CUSTOMISED INTERIOR LOCATION?

Thanks to the Bluetooth beacons, take advantage of a detailed and customizable indoor location according to the configuration of the site to be covered (floors, areas, corridors, etc.).

They are designed to communicate with all the alarm devices of the  $\operatorname{\mathsf{EMERIT}} \otimes$  range.





# e - WG100

### > Key alarm Features

### **4 WAYS TO TRIGGER ALARMS**

- SOS Alert Button
- No motion detection
- Tilt detection
- Fast wrist movements

#### **3 TYPES OF ALARM SCENARIO**

- Internal: Call and SMS
- Out-source: calls & protocole IP SIA DC-09 (1)
- Supervised: dedicated supervisory protocole IP SIA DC-09 (1)



- Satellites: out-door (2)
- Wifi: indoor (3)
- Bluetooth: indoor (3)

#### **ADVANCED FEATURES**

- Unlimited number of alert recipients on call and SMS
- Advanced setting of trigger modes (button-pressing mode, detection sensitivity, notification type and timeouts)
- Auto-test of the system at the start (3)
- Programmed by using web browser







Arm-band Smart fix system







Carabiner Smart-fix system

### > Technical specification

RADIO SET UP	
GSM (2G)	900 / 1800 MHz
WCDMA (3G)	2100 (B1) / 900 (B8) MHz
FDD-LTE (4G)	B1/B3/B7/B8/B20
Wifi	802.11n (Wifi 4)
Bluetooth	3.0
satellite Localisation	GPS & Glonass
A-GPS	Yes
MEMORY	
RAM	512 Mo
ROM	4 Go
SIM CARD	
1 slot	NanoSim

OTHER FEATURES	
Processor	Arm Cortex-A53 1.1 GHz
Battery	650 mAh lithium-ion polymer
Screen	1" TFT couleur
Connectivity	USB / magnetic 4-pin
Operating System	Android Oreo 8.1
Weight	53 g including wristbands & batter
Dimensions	58 x 42 x 16 mm
Dust water/tightness	IP65 <sup>(4)</sup> / standard CE
Vibrator	Yes
Micro and Loudspeaker	Yes
Specific absorption rate	
Head	0.21 W/Kg (limite 2 W/Kg)
Trunk	0.91 W/Kg (limite 2 W/Kg)

### **BOX CONTENT:**

- Watch
- Black silicone bracelet
  - Screwdriver
- Charge station
- USB charger
  - Quick start guide

#### OTHER ACCESORIES AVAILABLE:

- Smartfix system belt clip Black nylon bracelet
- Smart fix system for neck
- Bluetooth beacons for indoor location
  - Smartfix system Arm-band
- Smartfix system carabiner

### **MAGNETA**

189 rue d'Aubervilliers 75018 Paris -France

www.magneta.fr

SAS au capital de 215 000 -SIRET 339 529 489 00025 NAF 4652Z - RCS Paris B 339 529 489 - TVA FR 15 339 529 489

(1) Requires the underwriting of a specific service contract.

(2) GPS: Depending on the positioning of the device in a vehicle and/or on the user, weather conditions and urban density, the position may not be updated at the time of the alert or imprecise from several hundred meters.

(3) Wifi: precision dependent on the customer's Wi-Fi infrastructure.

Bluetooth: accuracy depending on the amount of tags implanted and their positioning.

(4) According to IEC 60529; fully protected against dust / protected against water jets from all directions at the lance (6.3 mm nozzle, distance 2.5 to 3 m, flow rate 12.5 I / min ± 5%). Splash, water and dust resistance is not a permanent condition.

It may decrease due to normal wear and tear and depending on the maintenance of the device. Damage caused by liquids is not covered by the warranty.

